

Spillage Vac



Technical Specifications

Voltage	24 Volt	Weight (product)	21 (+15) kg
Motor	550 Watt	Height	1350 mm
Material	PP-PE	Diameter accessories	ø 32 mm
Suction Power	1500 mm	Cable Length	—
Air Speed	32 L/sec	Capacity (paper bag)	50Ltr
Sound Level	50 dB	CBM	0.6296

FAST Europe B.V. | P.O. Box 28027 | 5602 JA | Eindhoven | NL

T +31 (0)40 266 24 90 | F +31 (0)40 266 24 99 | E sales@fastproducts.nl | W www.fastproducts.nl

Visiting address | Hoppenkuil 27 a | 5626 DD | Eindhoven | NL | Warehouse | Hoppenkuil 27 a | 5626 DD | Eindhoven

DUTCH
TECHNOLOGY
INSIDE

TO CLEAN QUICK THINK FAST

Spillage Vac


INDEX



K.1.22.9045.400G



K.10.32.0094.5
K.100.32.0094.5



K.2.32.0063.1



K.10.54.0015.1/2 (2-l)
K.100.54.0015.1/2 (2-l)
K.10.54.0016.1/5 (5-l)
K.100.54.0016.1/5 (5-l)



K.1.32.0064.1



K.1.S.30.0071.1



K.1.S.32.0483.25



K.1.S.30.0071.101



K.1.S.21.6342.18



K.1.SBT.FOM.2
K.2.60.0002.0

DUTCH
TECHNOLOGY
INSIDE

FAST Europe B.V. | P.O. Box 28027 | 5602 JA | Eindhoven | NL

T +31 (0)40 266 24 90 | F +31 (0)40 266 24 99 | E sales@fastproducts.nl | W www.fastproducts.nl

Visiting address | Hoppenkuil 27 a | 5626 DD | Eindhoven | NL | Warehouse | Hoppenkuil 27 a | 5626 DD | Eindhoven

TO CLEAN QUICK THINK FAST

Version: September 2010